



### GBH 2-26DFR Variable Speed Rotary Hammer

Rated power input: 800 W  
 Impact energy: 0 – 3 J  
 Impact rate at rated speed: 0 – 4.000 rpm  
 Rated speed: 0 – 900 rpm  
 Rated torque: 28 Nm  
 Weight: 2,7 kg  
 Toolholder: SDS-plus



### GBH 4 DFE Variable Speed Rotary Hammer

Impact/Rotation Stop  
 Quick Change Chuck, Carrying Case  
 Power Input 750W  
 No Load Speed 0-650 rev/min  
 Impact Rate/Force 0-3900/min 3.5J, Tool Holder SDS plus  
 Weight 3.9kg  
 Drilling Capacity      Concrete 30mm  
                                  Masonry 80mm



### GBH 4 DSC SDS Plus Combi-hammer

Rated power input: 750 W  
 Impact energy: 1 – 3,5 J  
 Power output: 440 W  
 Impact rate at rated speed: 1.650 – 3.900 rpm  
 Rated speed: 280 – 650 rpm  
 Rated torque: 20 Nm  
 Weight: 5,9 kg  
 Number of needles: 19  
 Usable needle length: 60 mm  
 Toolholder: SDS-plus



### GSR 14-2 14V Drill/Driver

Torque, max. (hard screwdriving applications): 30 Nm  
 No-load speed, 1st gear: 0 – 400 rpm  
 No-load speed, 2nd gear: 0 – 1.400 rpm  
 Torque, max. (soft screwdriving applications): 11 Nm  
 Battery type: NiCd  
 Chuck jaw width, min./max.: 1 / 10 mm  
 Battery voltage: 14,4 V  
 Battery capacity: 1,5 Ah  
 Charging time, approx.: 60 min



### GSB 14.4VE-2 14.4V Combination Cordless Drill

Torque, max. (hard screwdriving applications): 65 Nm  
 Torque, max. (soft screwdriving applications): 28 Nm  
 Impact rate, max.: 29.000 rpm  
 Chuck jaw width, min./max.: 1,5 / 13 mm  
 Drill spindle thread: 1/2"      Torque settings: 25+1  
 Battery voltage: 14,4 V  
 Weight including battery, approx.: 2,80 kg  
 Quick change chucks: 13 mm Charging time, approx.: 30 min  
 Max. drilling diameter in wood: 40 mm  
 Max. drilling diameter in steel: 13 mm  
 Max. drilling diameter in masonry: 14 mm

